



Spray-Lining
1-855-545-4900
9 E Lookerman Street
Dover, DE 19901

Section 1: Company Information

MATERIAL SAFETY DATA SHEET

Spray-Lining
9 E lookerman St
Dover, De 19009
1-855-545-4900

24 HOUR EMERGENCY: CHEMTREC 800-424-9300

Product Name: SLC-208-E

Section 2: HAZARDS IDENTIFICATION

Name	CAS#	%	ACGIH TLV (PPM)	OSHA PEL (PPM)
Oxazolidene Family Amine	97553-90-7	0.1 – 0.2	NA	3

This amine is classified as a formaldehyde donor, which is listed as carcinogen.
NA – Not Applicable

Section 3: Physical Data

Boiling Range: 212°F Vapor Density Heavier Lighter than Air

Evaporation Rate	Percent volatile by volume	Weight per gallon
<input type="checkbox"/> Faster <input checked="" type="checkbox"/> Slower than ether	45-85	8.5 – 11 Lbs

Appearance and odor : milky liquid with slight ammoniacal odor

Section 4: Fire and Explosion Data

DOT Category : Not Regulated **Flash Point:** N.A. **LEL:** N.A.

Extinguishing Media: N.A.

Special FireFighting Procedures: N.A.

Unusual Fire & Explosion Hazards: N.A.

Hazardous decomposition Products: May form toxic materials – carbon monoxide - carbon dioxide and nitrogen oxides

Target Organ Information: Overexposure may cause damage to skin and respiratory system.

Reportable Spill Information: Not reportable to the National Response Center



Section 5 : Health Hazard Data

Effects of overexposure

Eyes

Can cause irritation, redness
Tearing, blurred vision

Skin

Can cause moderate irritation,
defatting, dermatitis.

Inhalation

Can cause nausea and headache

Ingestion

Can cause gastrointestinal irritation
And nausea.

First Aid

Flush with large amounts of water, lifting upper
and lower lids occasionally, get medical attention.

Thoroughly wash exposed area with soap and
Water. Remove contaminated clothing. Launder
contaminated clothing before re-use.

Remove individual to fresh air

Induce vomiting, keep person warm, quiet and get
Medical attention.

Section 6 : Reactivity Data

Steps to be taken in case material is released or spilled

Small Spill: Absorb liquid on paper, vermiculite, floor absorbent, or other absorbent material and transfer to ventilated closure.

Large spill: Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks, etc.). Persons not wearing protective equipment should be excluded from area of spill. Stop spill at source, dike area of spill to prevent spreading, pump liquid to salvage tank. Remaining liquid may be taken up on sand, clay, earth, floor absorbent or other absorbent material and shoveled into containers.

Waste disposal method: Dispose of in accordance with local state and federal regulations.

Section 7: Special Protection Information

Respiratory Protection: If TLV of the product is exceeded, a NIOSH/MESA jointly approved self-contained breathing apparatus with a full face piece operated in pressure demand or other positive Niosh/Mesa respirators under specified conditions. (see your safety equipment supplier).

Ventilation: Provide sufficient mechanical (general) and/or local exhaust ventilation to maintain exposure below TLV's.

Protective Gloves: Wear resistant gloves such as Buna-N.

Eye Protection: Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. (See your safety equipment supplier)



Spray-Lining

1-855-545-4900

9 E Lookerman Street

Dover, DE 19901

Other protective equipment: To prevent repeated or prolonged skin contact wear impervious clothing and boots.

Section 8 : Special Precautions

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid) all hazard precautions given in this data sheet must be observed.

Keep out of reach of children.